

CS6205

Copolymer Blending Resin

CS6205 is a VCM/VAM copolymer blending resin made by the suspension polymerization process. **CS6205** is used in mixtures with emulsion or microsuspension resins blending up to 50 phr in order to make low viscosity plastisols with low gelation and fusion temperatures.

Applications	Plastisol
Vinyl lacquers and adhesives	•
Automotive sealant	•
Carpet backing	•
Dip coating, slush and rotomolding	•

■ recommended ○ feasible

Properties	Method	Units	Value
K Value	DIN 53726	-	62 ± 1
Appearance	ISO 1159-78F		White Powder
Bounded Vinyl Acetate, %	ASTM D 1243	-	4-6
Particle Size	ASTM D 1921		
 Retained on Mesh 200 		%	3 max.
Volatile Content	ASTM D 3030	%	1.0 max.

Main properties of CS6205 are:

- Small particle size. and tight particle size distribution.
- Reduces viscosity and dilatancy.
- Improves air release properties.
- Increases gelation rates.
- Decreases the stiffness of the article.
- Decreases processing temperatures.

Presentation

CS6205 is available in 25 kg multilayer paper bags.

Storage Conditions

It should always be stored in their original package, in a dry, cool place with good ventilation, and protected from solar radiation.

Qualification Certficates

ISO 9001, ISO 14001, Ohsas 1801, Level 7- ISRS. Edition 6.

Mexichem | Mamonal Km. 8 C.P. 130013 | Cartagena | Colombia | T. (575) 6723150 | www.mexichemresins.com

This information is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third part patent rights, no guarantee of properties in the legal sense is implied. We reserve the right to make any change according to technical progress of further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Reference to trade names used by other trade names by other companies neither recommendation, nor is intended to suggest that similar products could be used. All our business transactions shall exclusively be governed by our General Sales Conditions.

Version 7|2019